

Refridgeration dryers

HFQ SERIES

BENEFITS AND FEATURES

- Frequency controlled: Low energy consumption
- Well-proven branded components
- Long service life
- Short payback time



Technical Data	1200 & 1400	1700 & 1900	2200 - 5000
Inlet / Outlet	Left		Rear
Bypass	○		○
Refrigerant	R 134a	R 407A	R 407A
Air cooling	●		●
Water cooling	○		
Heat Exchanger	Stainless steel plates (copper welded)		
IP rating	IP23		IP44
Dew point indication	Digital LED, with alarm lamp		Digital
Potential free alarm contact	○		●
Electronic level controlled drain	●		

General Data	
Medium	Compressed Air
Housing	Steel
Colour - Top Panel	RAL 9001 (white), powder-coated
Colour - Housing	Grey, powder-coated
Location	Indoors

Design Data*	Min.	Nom.	Max.
Operating pressure	3 bar (g)	7 bar (g)	16 bar (g)
Inlet temperature	+4 °C	+35 °C	+50 °C
Ambient temperature	+3 °C	+25 °C	+45 °C


* The correction factors on the back need to be used to select the correct unit for other operating conditions.
Hankison® refrigerant compressed air dryers are best used with a Hankison® PF pre-filter and a HF after-filter.

Model	Flow Rate*	Connection	Dimensions			Weight	el. Connection	Power Consumption at 100%
			A	B	C			
				mm			V/Ph/Hz	kW
HFQ 1200	1,200	R 2 1/2"	1,129	857	1,510	330	400/3/50 460/3/60	2.1
HFQ 1400	1,400					345		2.7
HFQ 1700	1,700					370		4.3
HFQ 1900	1,900	R 3"	1,131			400		5.2
HFQ 2200	2,200	DN 100	1,243	1,386	2,116	690	400/3/50 460/3/60	5.3
HFQ 2400	2,400					690		6.7
HFQ 3200	3,200	DN 150	1,400	1,584	2,112	880	400/3/50 460/3/60	8.6
HFQ 3650	3,650					880		9.3
HFQ 4600	4,600					1,050		10.5
HFQ 5000	5,000					1,200		13.5

* ISO 7183, based on the intake volume of the compressor at +20°C and 1 bar (a), operating pressure 7 bar (g), inlet temperature +35°C, ambient or cooling water temperature +25°C, pressure dew point +3°C
 Technical data and specification are subject to change without prior notice

Comparison Frequency-controlled / Standard dryer						
Power Consumption						
Model	FQ controlled (range)	up to 30 % load	at 40 % load	at 60 % load	at 80 % load	at 100 % load
kW		kW	kW	kW	kW	kW
HFQ 1200	0.8 – 2.1	0.8	1.1	1.4	1.8	2.1
HFQ 1400	0.8 – 2.7	0.8	1.2	1.7	2.3	2.7
HFQ 1700	1.5 – 4.3	1.5	1.7	2.4	3.6	4.3
HFQ 1900	1.5 – 5.2	1.5	1.9	2.8	4.2	5.2
HFQ 2200	2.0 – 5.3	2.0	2.3	3.3	4.5	5.3
HFQ 2400	2.0 – 6.7	2.0	2.7	3.9	5.6	6.7
HFQ 3200	3.1 – 8.6	3.1	3.9	5.0	7.2	8.6
HFQ 3650	3.1 – 9.3	3.1	4.2	5.3	7.8	9.3
HFQ 4600	3.9 – 10.5	3.9	4.5	6.1	9.5	10.5
HFQ 5000	3.9 – 13.5	3.9	5.2	7.5	11.2	13.5

Note: The word „load“ (%) not only means the flow rate, but especially the warming level of the incoming pressured air.



Calculation example:		HFQ 3650	
Working hours/year:	8,700	Power Consumption at 100 % load	Power Consumption at 40 % load
Costs kWh in €:	0.12	9.3 kW	4.2 kW
Calculation:		9.3 · 8,700 · 0.12	4.2 · 8,700 · 0.12
Working hours in € per year:		9,709	4,385

The following correction factors need to be used to select the correct unit for other operating conditions.

Correction factors for different operating pressures in bar(g) (F ₁)														
bar (g)	3	4	5	6	7	8	9	10	11	12	13	14	15	16
HFQ 1200 – 5000	0.79	0.87	0.92	0.96	1.00	1.03	1.07	1.10	1.13	1.16	1.18	1.21	1.24	1.27

Correction factors for different inlet temperatures in °C (F ₂)				
°C	+35	+40	+45	+50
HFQ 1200 – 5000	1.00	0.85	0.71	0.63

Correction factors for different ambient temperatures in °C (F ₃)					
°C	+25	+30	+35	+40	+45
HFQ 1200 – 5000	1	0.94	0.89	0.83	0.78

Selection example		Calculation	
Compressor capacity (V ₁)	1,100 m ³ /h	$V_2 = \frac{V_1}{F_1 \cdot F_2 \cdot F_3} = \frac{1,100}{0.8 \cdot 1.10 \cdot 0.89} = 1,582 \text{ m}^3/\text{h}$	Selection: HFQ 1700
Operating pressure (F ₁)	10 bar (g)		
Inlet temperature (F ₂)	+45 °C		
Ambient temperature (F ₃)	+35 °C		
V ₂	Required dryer capacity		

SPXFLOW



SPX Flow Technology Germany GmbH
 Konrad-Zuse-Straße 25 | D-47445 Moers
 Tel.: +49 (0) 28 41 / 8 19-0 | Fax: +49 (0) 28 41 / 8 19 83
 E-Mail: info@spx-hankison.de
 www.spx-hankison.de | www.spxflow.com

SPX FLOW, Inc. reserves the right to incorporate our latest design and material changes without notice or obligation.

Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing. Please contact your local sales representative for product availability in your region. For more information visit www.spxflow.com.

The green 'S' and 'X' are trademarks of SPX FLOW, Inc.